

**Product Information** 

BPAC406

## **BestPrimer AC406** Modified polyacrylic primer, one component.

Feb. 2020 version

BestPrimer AC406 is a modified polyacrylic based compound, one component, specialized to used in specific application, in order to reinforce the surface, enhance the bonding strength.
BestPrimer AC406 is applied as the primer on the surface of concrete or motar before appling products as self-leveling polymer-cement motar, polymer-cement, polyacrylic, polyurethane based waterproofing compound or sealant, of items such as: the floor, eaves, terrace, balcony, bathroom, basement,
<ul> <li>High permeability should be able to link inside the material deeply.</li> <li>High adhesion to cement-based materials.</li> <li>Easy to apply by popular tools such as brush, roller, spray</li> <li>Non-toxic, non-odor, friendly with environment.</li> </ul>
5kg, 25kg/ can or 210 kg/drum.
12 months upon manufacturing date (In original, unopened package) ; In cool , dry place
Liquid emulsion
Milk white
$0.10 \div 0.20 \text{ kg/m}^2$ (depends on surface condition)
Minimum: 10°C (Above dew point at least 5°C) <b>re:</b> Maximum: 35°C (Maximum permissible relative humidity: 80%)
<i>i</i> : Significantly enhanced adhesion and sealing of the surfaces.
30 mins @ 25°C, in space working place.
1.03 ± 0.01 kg/liter (25°C)

**BESTMIX CORPO** www.bestmix.vn HEAD OFFICE:

Lot D1, D18N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province, Tan Binh Dist., Ho Chi Minh City Tel: (027) 4365 3990 - 4365 3991 Tel: (028) 3810 7995 (7996, 7997) Tel: (028) 3899 0339 - 3899 0340 Email: info@bestmix.com.vn

HCMC OFFICE 1: Email: bm1@bestmix.com.vn HCMC OFFICE 2: Email: bm2@bestmix.com.vn NHA TRANG OFFICE: 989 Le Hong Phong Street, Phuoc Long Ward, Nha Trang City Tel: 090 545 3579 Email: bm3@bestmix.com.vn

**CENTRAL BRANCH:** 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City Tel: (023) 6371 5299 - 6371 5399 Email: bm4@bestmix.com.vn

NORTHERN BRANCH: TT6.2 - 65, Dai Kim Urban Area, Hoang Mai Distrist, Ha Noi City Tel: (024) 3200 8234 Email: bm5@bestmix.com.vn

	BPAC406 Page 2/2
Applycation :	
General requirement:	<ul> <li>For the high absorbing or breakable surface: should add more 5% clean water and mix well before applying.</li> <li>For the average rough, dense and flat surface: do not add water.</li> <li>For high smooth rubbed suface: texture suface and clean before usi BestPrimer AC406</li> </ul>
Surface condition:	Concrete (or mortar) must reach compressive strength and tens strength for the work items requirement. The surface should be no free water, ponding areas should be dry with clean cloth. Impurities, debris, dirt, grease, algae, mold must be cleaned required.
Application:	Apply by roller, pressure sprayer or brush with the consumption 0.10 + 0.20 kg/m <sup>2</sup> (depends on surface conditions). Materials must be evenly spread to get the highest effectiveness. When applying the next layer, to ensure the primer be completely of lining (transparent, hard and no longer sticky). <b>Attention:</b> Do not let the puddles appear. After applying 05 to 10 minutes, check the surface. If you find that the state has not switched to transparent (structure) at the location of the puddle, must spread puddles by roller brush. The working place must be peaceful. Stir well before using
Cleaning:	Clean tools and equipment immediately after applying soap, and cle water.
Safety:	The product is harmless, non-flammable This product can be allergic to the skin. Avoid prolonged skin conta Protective clothing is highly recommended. In case of contact with the eyes, rinse immediately with plenty of cle water and seek medical advice. Working place should be peaceful and cool

**Disclaimer:** 

The technical information and application instruction in documents of BESTMIX based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of product, so users should test the product for each purpose. BESTMIX has the right to change features of our product, user must always refer the latest technology product.

## **BESTMIX CORPORATION**

www.bestmix.vn 
 HEAD OFFICE: Lot D1, D1&N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province, Tel: (027) 4365 3990 - 4365 3991
 HCMC OFFICE 1: 378-384 Cong Hoa Str., Ward 13, Tan Binh Dist., Ho Chi Minh City Tel: (028) 3810 7995 (7996, 7997)
 HCMC OFFICE 2: 23 Nguyen Huu Canh Str., Ward 22, Binh Thanh Dist., Ho Chi Minh City Tel: (028) 3810 7995 (7996, 7997)
 HEAD OFFICE: Email: info@bestmix.com.vn

## Email: bm1@bestmix.com.vn

Email: bm2@bestmix.com.vn

NHA TRANG OFFICE: 989 Le Hong Phong Street, Phuoc Long Ward, Nha Trang City Tel: 090 545 3579 Email: bm3@bestmix.com.vn

**CENTRAL BRANCH:** 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City Tel: (023) 6371 5299 - 6371 5399 Email: bm4@bestmix.com.vn

NORTHERN BRANCH: TT6.2 - 65, Dai Kim Urban Area, Hoang Mai Distrist, Ha Noi City Tel: (024) 3200 8234 Email: bm5@bestmix.com.vn

= | =