

BHSS115



Mar. 2023 Version

BestHard SS115 Surface hardener, dustproof compound for concrete.

Description:	BestHard SS115 is an one-component sodium silicate compound that strengthens concrete surface hardness, especially for concrete floors and floors, increasing wear resistance, resistance to dust generation in concrete use.
Recommended for:	Floors of industrial factories, warehouses, garages, parking lots, places with high requirements for anti-wear, anti-dust generation for concrete surfaces.
Advantages:	 Ready to use. Easy to apply. Improved chemical and abrasion resistance compared to untreated concrete. Anti- dust. Improves cleanability. Non-yellowing. Good penetration. Improve hardness. Solvent free. Colourless and odourless. Do not change the floor's color. Apply in both outdoor and indoor. Environmentally friendly.

PRODUCT DATA:

Appearance:	Viscous liquid.
Color:	Semi-transparent.
Packing:	25liters/can ; 210l/drum, 1000l/tank.
Storage:	In cool and dry places, at temperatures between 5°C and 30°C.
Shelf life:	24 months, if stored properly in original.
Active content:	≥ 18.5 %.
Density	1.15 ±0.05 kg/l
рН	11.0 ± 1.0
Consumption:	10 \div 20 m ² /L (depending on the concrete status).
Dilution ratio:	Undiluated

Dilution ratio: Undiluated

BESTMIX CORPORATION

www.bestmix.vn HEAD OFFICE: Lot D1, D1&N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province. Tel: (027) 4365 3990 - 4365 3991 Email: info@bestmix.com.vn

HCMC OFFICE 1:
 378-384 Cong Hoa Str., Ward 13, Tan Binh Dist., Ho Chi Minh City
 23 Nguyen Huu Canh Str., Ward 22, Binh Thanh Dist., Ho Chi Minh City

 Tel: (028) 3810 7995 (7996, 7997)
 Tel: (028) 3899 0339 - 3899 0340
 Email: bm1@bestmix.com.vn

HCMC OFFICE 2:

Email: bm2@bestmix.com.vn

NHA TRANG OFFICE: 989 Le Hong Phong Street, Phuoc Long Ward, Nha Trang City Tel: 090 545 3579 Email: bm3@bestmix.com.vn

CENTRAL BRANCH: 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City Tel: (023) 6371 5299 - 6371 5399 Email: bm4@bestmix.com.vn

NORTHERN BRANCH: TT6.2 - 65, Dai Kim Urban Area, Hoang Mai Distrist, Ha Noi City Tel: (024) 3200 8234 Email: bm5@bestmix.com.vn



BHSS115

Abrasion Resistance:	$25 \div 40\%$ increase in abrasion resistance (depend on surface condition).
Permeability:	2.0 ÷ 7.0 mm (depend on surface condition).
Application temperature:	Minimum: +10ºC (above dew point temperature of 5ºC) Maximum: + 40ºC Relative humidity ≤ 80%
APPLICATION:	
Surface preparation:	Surfaces must be sound, open textured, clean, free from frost, laitance, surface water, oils, grease, coatings, all loosely adhering particles and other surface contaminants. In order to allow the material to penetrate deeply, concrete should be dried to the appropriate moisture content (≤8%).
Placing:	Use a roller or low pressure sprayer to evenly speard the material to the surface according to the appropriate rate (depending on the surface status). After about 30 minutes (when the material begins to gel), use a clean water jet to spray an appropriate amount of water just enough to re-disperse (with a brush or a scrubber) the remaining material on the surface. Once the surface begins to dry again, rinse with water jet and dry with a wet rag or vacuum cleaner. When there is a need to polish the surface, it is recommended to use BestSlick G85 polishing compound to increase the aesthetics of the concrete surface.
Cleaning:	Clean all tools and application equipment with clean water immediately after placing and before the material hardens.

Disclaimer:

The technical information and application instructions in documents of BESTMIX are based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of product, so users should test the product for each purpose. BESTMIX has the right to change the features of our product, user must always refer the latest technology product.

BESTMIX CORPORATION

www.bestmix.vn HEAD OFFICE: Lot D1, D1&N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province. Tel: (027) 4365 3990 - 4365 3991

Email: info@bestmix.com.vn

HCMC OFFICE 1: 378-384 Cong Hoa Str., Ward 13, Tan Binh Dist., Ho Chi Minh City Tel: (028) 3810 7995 (7996, 7997)

Email: bm1@bestmix.com.vn

HCMC OFFICE 2:

23 Nguyen Huu Canh Str., Ward 22, Binh Thanh Dist., Ho Chi Minh City Tel: (028) 3899 0339 - 3899 0340 Email: bm2@bestmix.com.vn

NHA TRANG OFFICE: 989 Le Hong Phong Street, Phuoc Long Ward, Nha Trang City Tel: 090 545 3579 Email: bm3@bestmix.com.vn

CENTRAL BRANCH: 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City Tel: (023) 6371 5299 - 6371 5399 Email: bm4@bestmix.com.vn

NORTHERN BRANCH: TT6.2 - 65, Dai Kim Urban Area, Hoang Mai Distrist, Ha Noi City Tel: (024) 3200 8234 Email: bm5@bestmix.com.vn