



BestRelease S100

Form Release agent, organic solvent base

Mar 2018 Version

Description:

BestRelease S100 is an organic compound, Polyfin solvent base, use to release the form of the shaping product or pouring concrete. To make shaping material and form do not stick together, and easily remove the mold.

Recommended for:

Used as form release agent for metal mold, plastics, wood,...in the pouring concrete.

Used as form release agent for shaping the fine art products.

Advantages:

- Anti-stick form optimal.
- Improve the quality of the product surface after shaping.
- Protect the form is not damaged in the process of releasing the shaping material from the form.
- Does not contain corrosive material affect the shaping material as well as form.
- Low viscosity, easy to use.
- Non-toxic.

Technical data:**Existence form:**

Liquid.

Color:

Light yellow.

Density:

0.99 ± 0.02 kg/liter.

Storage conditions:

In a cool and dry place, avoid contacting directly with the fire.

Shelf life:

At least 12 months.

Package:

5L, 25L/ can, 210L/ drum.

Consumption:

To metal and plastic form : 20 – 30 m² /liter
To wood form : 10 – 15 m² / litter

HEAD OFFICE:

Lot D1, D1&N3 Rd., Nam Tan Uyen IP,
Tan Uyen Town, Binh Duong Province.
Tel: (027) 4365 3990 - 4365 3991
Email: info@bestmix.com.vn

HCMC OFFICE 1:

378-384 Cong Hoa Str., Ward 13,
Tan Binh Dist., Ho Chi Minh City
Tel: (028) 3810 7995 (7996, 7997)
Email: bm1@bestmix.com.vn

HCMC OFFICE 2:

23 Nguyen Huu Canh Str., Ward 22,
Binh Thanh Dist., Ho Chi Minh City
Tel: (028) 3899 0339 - 3899 0340
Email: bm2@bestmix.com.vn

NHA TRANG OFFICE:

989 Le Hong Phong Street,
Phuoc Long Ward, Nha Trang City
Tel: 090 545 3579
Email: bm3@bestmix.com.vn

CENTRAL BRANCH:

478B1 Dien Bien Phu Street,
Thanh Khe District, Da Nang City
Tel: (023) 6371 5299 - 6371 5399
Email: bm4@bestmix.com.vn

NORTHERN BRANCH:

TT6.2 - 65, Dai Kim Urban Area,
Hoang Mai District, Ha Noi City
Tel: (024) 3200 8234
Email: bm5@bestmix.com.vn

| | |
|-----------------------------|--|
| Conditional surface: | <p>The form surface should be cleaned before applying.</p> <p>Dirt and mud should be washed or cleaned.</p> <p>Grease, oil or old material should be cleaned by proper solvent when using BestRelease S100 first.</p> |
| Application: | <p>Use a brush, roller, or injector to apply evenly BestRelease S100 on the forming surface before applying the shaping product.</p> <p>Do not apply surplus BestRelease S100, to avoid BestRelease S100 mixing into the shaping material, reducing the quality of the shaping material as well as waste materials.</p> <p>Should apply BestRelease S100 before shaping at least 15 minutes</p> <p>Do not let BestRelease S100 contact directly with the reinforcement of the product.</p> |
| Cleaning, safety: | <p>Clean all tools and application equipment with a cloth immediately after use.</p> <p>BestRelease S100 is flammable so stay out of the heat or fire</p> <p>Avoid contacting directly food, or instruments of live activity, and keep out of the reach of children.</p> <p>In case of accidental eye contact, wash with fresh water and seek medical advice immediately.</p> |

| | |
|--------------------|---|
| Disclaimer: | <p><i>The technical information and application instruction in documents of BESTMIX are based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of the product, so users should test the product for each purpose. BESTMIX has the right to change the features of our product, user must always refer the latest technology product.</i></p> |
|--------------------|---|